

AERODROME CHART - ICAO

HAMADAN

Scale 1 : 12000

200M 0 200 400 600 800
500FT 0 500 1000 1500 2000 2500

Hot spot 1:
Caution vehicle movement.

Hot spot 2:
Ultra light ACFT taxiing have to maintain a good look out at all times due to helicopter operation and vehicles movement.

Hot spot 3:
All ultra light ACFT ,helicopters and vehicles shall hold short of RWY 10.

Aerodrome Elevation : 5771 FT

Aerodrome Lighting	
RWY 10	RWY 28
SALS	SALS Barrette
PAPI	PAPI
RTHL	RTHL
REDL	REDL
RENL	RENL
STWL	STWL
WBAR	

ABN : FLG White, Green
Apron : INFO not AVBL

TWY Lighting	
Edge : All TWYs	
Center Line : NIL	

ATS Communication Facilities	
Service Designation	Frequency
TWR	123.500, 121.900,
-	-
-	-

AD Reference Code : 4D

Displaced Threshold	
DTHR RWY 10 : Coordinates: 345213.36N 0483232.75E Displaced: 300 M Elevation: 5705 FT	

RWY	Direction	Elevation	THR Coordinates	GUND	Bearing Strength (PCN) and Surface
10	104.88°	5703 FT	345215.86N 0483221.35E	+ 33 FT	62/F/C/X/T Asphalt
28	284.90°	5771 FT	345144.18N 0483445.91E	+ 33 FT	62/F/C/X/T Asphalt
-	-	-	-	-	-
-	-	-	-	-	-

VOR check point NIL

TWY	Width : 25 M Surface : Asphalt Strength (PCN) : 58/F/C/X/T
Apron	Surface : Asphalt Strength (PCN) : 58/F/C/X/T Dimensions : 300 x 130 M

Apron
Taxiway
Runway
Building
Hotspot
Isolated ACFT Parking Position
Deicing Pad
Under Construction

