

Scale 1:11000

200M

0

200

400

600M

500FT

0

500

1000

1500

2000FT

Hotspot : NIL

Aerodrome Elevation : 5380 FT

Aerodrome Lighting

RWY 12

RWY 30

RTHL
WBAR
PAPI
REDL
RENL
STWL

SALS
RTHL
WBAR
PAPI
REDL
RENL
STWL

ABN : FLG White, Green

Apron : Edge Lighted

TWY Lighting

Edge : TWY A

Center Line : NIL

ATS Communication Facilities

Service Designation

Frequency

-

--

-

--

AFIS (Information)

122.950, 121.750

AD Reference Code : 4C

Displaced Threshold

NIL

RWY

Direction

Elevation

THR Coordinates

GUND

Bearing Strength (PCN) and Surface

12

126.51°

5308 FT

364657.94N 0482038.80E

+ 37 FT

50/F/B/X/T Asphalt

30

306.52°

5380 FT

364556.19N 0482222.51E

+ 37 FT

50/F/B/X/T Asphalt

-

-

-

-

-

-

-

-

-

-

-

-

VOR check point

NIL

TWY

Width : TWY A and B are 23 M.

Surface : Asphalt

Strength (PCN) : INFO not AVBL

Apron

Surface : Asphalt

Strength (PCN) : INFO not AVBL

Dimensions : 120M x 200M.

Apron

Taxiway

Runway

Building

Hotspot

Isolated ACFT Parking Position

Deicing Pad

Under Construction

CIVIL AVIATION ORGANIZATION

Changes: Apron, TWY and Turn pad Lights

AIRAC AMDT 2/25