

STANDARD DEPARTURE CHART-
INSTRUMENT (SID)-ICAO


TRANSITION ALTITUDE
11000 FT

TWR 118.100, 119.400
121.900
ATIS 128.450

ZAHEDAN
RWY 35L/R, 17L/R
DEBRO 1J/1H
PUVMI 1J/1H

ALL DIRECTIONS ARE MAGNETIC.
LEVEL AND ELEVATIONS ARE IN FEET.
DISTANCES ARE IN NAUTICAL MILES.

CTR and ATZ class "D".



DERBO 1J DEP:

DEP RWY 35L/R - After take off climb on TR 350° MAG to 6000 FT, then turn left to cross overhead ZD NDB at or above 8000 FT, then intercept BRG 095° to cross DERBO and climb to cleared level.
MNM rate of climb 320 FT/NM up to overhead ZD NDB. Turn below 6000 FT is not authorized.

DERBO 1H DEP:

DEP RWY 17L/R - After take off climb on TR 170° MAG to 6400 FT, then turn left to cross overhead ZD NDB at or above 8000 FT, then turn right to intercept BRG 095° to cross DERBO and climb to cleared level.
MNM rate of climb 260 FT/NM up to overhead ZD NDB. Turn below 6400 FT is not authorized.

PUVMI 1J DEP:

DEP RWY 35L/R - After take off climb on TR 350° MAG to 6000 FT, then turn left to cross overhead ZD NDB at or above 8000 FT, then turn right to intercept BRG 241° to PUVMI and climb to cleared level.
MNM rate of climb 320 FT/NM up to overhead ZD NDB. Turn below 6000 FT is not authorized.

PUVMI 1H DEP:

DEP RWY 17L/R - After take off climb on TR 170° MAG to 6400 FT, then turn left to cross overhead ZD NDB at or above 8000 FT, then turn left to intercept BRG 241° to PUVMI and climb to cleared level.
MNM rate of climb 260 FT/NM up to overhead ZD NDB. Turn below 6400 FT is not authorized.