

STANDARD DEPARTURE CHART-
INSTRUMENT (SID)-ICAO

TRANSITION ALTITUDE 6000 FT
TRANSITION LEVEL FL 80

INFO 122.100

LAVAN ISLAND/ LAVAN
RWY 11/29
LAM 2A/2B

ALL DIRECTIONS ARE MAGNETIC,
LEVEL AND ELEVATIONS ARE IN FEET,
DISTANCES ARE IN NAUTICAL MILES.

ATZ class "G".

LAMERD
VOR/DME
117.0 LAM
CH 117X



LAM 2A/2B

R343

AT 2000'

LAM 2A

R266

LAM 2A/2B
CROSS DVOR/DME AT
OR ABOVE 4000 FT

LAVAN
DVOR/DME
116.85 LVA
CH 115Y


LAM 2B

R106

AT 2000'



NOT TO SCALE



LAM 2A DEP:

DEP RWY 29 - After take off climb on RDL 266 TO 2000 FT, then turn left to cross overhead DVOR/DME at or above 4000 FT, then intercept RDL 343 to LAM VOR/DME and climb to cleared level. MNM rate of climb 260 FT/NM. This SID penetrates ODI110.

LAM 2B DEP:

DEP RWY 11 - After take off climb on RDL 106 TO 2000 FT, then turn right to cross overhead DVOR/DME at or above 4000 FT, then intercept RDL 343 to LAM VOR/DME and climb to cleared level. MNM rate of climb 260 FT/NM.