

AERODROME CHART - ICAO

ARAK

Scale 1 : 13000

200M

0

200

400

600

800

500FT

0

500

1000

1500

2000

2500

N

VAR 5°E

Hotspot : NIL

Aerodrome Elevation : 5453 FT

Aerodrome Lighting

RWY 08

RWY 26

RTHL

REDL

RENL

STWL

SALS

RTHL

PAPI

REDL

RENL

STWL

ABN : FLG White, Green

Apron : INFO Not AVBL

TWY Lighting

Edge : Lighted

Center Line : NIL

ATS Communication Facilities

Service Designation

Frequency

--

--

--

--

--

--

AFIS (Information)

118.650 , 121.850

AD Reference Code : 4D

Displaced Threshold

NIL

RWY

Direction

Elevation

THR Coordinates

GUND

Bearing Strength (PCN) and Surface

08

079.21°

5447 FT

340806.07N 0494939.48E

+ 20 FT

65/F/C/X/T Asphalt

26

259.24°

5453 FT

340828.52N 0495201.32E

+ 20 FT

65/F/C/X/T Asphalt

VOR check point

NIL

TWY

Width : 23 M

Surface : Asphalt

Strength (PCN) : 65/F/C/X/T

Apron

Surface : Asphalt

Strength (PCN) : 65/F/C/X/T

Dimensions : 150 x 75 M

Apron

Taxiway

Runway

Building

Hotspot

Isolated ACFT Parking Position

Deicing Pad

Under Construction

CIVIL AVIATION ORGANIZATION

Changes: New

AIRAC AMDT 2/26