

AD 2. AERODROMES**OIHS AD 2.1 AERODROME LOCATION INDICATOR AND NAME****OIHS - HAMADAN - NOGEH / Military****OIHS AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	<i>ARP coordinates and site at AD</i>	351210N 0484000E
2	<i>Direction and distance from (city)</i>	NNE, 25 NM from Hamadan
3	<i>Elevation / Reference temperature</i>	5613 FT / 34.2°C
4	<i>MAG VAR / Annual change</i>	3°30' E (1997)
5	<i>AD Administration, address, telephone, telefax, telex, AFS</i>	Islamic Republic Iranian Air Force (IRIAF)
6	<i>Types of traffic permitted (IFR/VFR)</i>	IFR/VFR
7	<i>Remarks</i>	PPR from IRIAF

OIHS AD 2.3 OPERATIONAL HOURS**H24****OIHS AD 2.4 HANDLING SERVICES AND FACILITIES**

2	<i>Fuel / oil types</i>	JP4, 100LL
---	-------------------------	------------

OIHS AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

<i>Designations RWY NR</i>	<i>TRUE & MAG BRG</i>	<i>Dimensions of RWY (M)</i>	<i>Strength(PCN) and surface of RWY and SWY</i>	<i>THR coordinates</i>	<i>Remarks</i>
1	2	3	4	5	
05	NIL	3962 x 45	LCN 70 Asphalt	NIL	Other information is not available
23	NIL	3962 x 45	LCN 70 Asphalt	NIL	
13	NIL	4457 x 45	LCN 70 Asphalt	NIL	
31	NIL	4457 x 45	LCN 70 Asphalt	NIL	

OIHS AD 2.14 APPROACH AND RUNWAY LIGHTING

APCH, RWY edge, RWY end and THR lighting available

OIHS AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

3	<i>TWY edge and centre line lighting</i>	Edge lighted
---	--	--------------

OIHS AD 2.18 ATS COMMUNICATION FACILITIES

<i>Service designation</i>	<i>Call sign</i>	<i>Frequency</i>	<i>Hours of operation</i>	<i>Remarks</i>
1	2	3	4	5
APP	Nogeh Approach	119.100 MHZ 125.450 MHZ 353.800 MHZ 385.400 MHZ 361.100 MHZ 344.000 MHZ 317.500 MHZ	H24 H24 H24 H24 H24 H24 H24	Emergency UDF
TWR	Nogeh Tower	123.300 MHZ 275.800 MHZ 257.800 MHZ	H24 H24 H24	

OIHS AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, CAT of ILS (For VOR/ILS, give VAR)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
NDB	HAB	329 KHZ	H24	351200.0N 0484000.0E		
VOR (3°30' E / 1997)	HAB	115.400 MHZ	H24	351234.0N 0483931.0E		
TACAN	HAB	CH 101X	H24	351234.0N 0483931.0E		

TACAN unusable in counter clockwise direction at 40 DME in the FLW area:

1- 030°- 240° BLW 12000FT AMSL.	4- 170°- 160° BLW 11000FT AMSL.
2- 240°- 220° BLW 11500F TAMS.	5- 160°- 080° BLW 10000FT AMSL.
3- 220°- 170° BLW 13000FT AMSL.	6- 080°- 030° BLW 11500FT AMSL.