

STANDARD DEPARTURE CHART-
INSTRUMENT (SID)-ICAO




TRANSITION LEVEL
FL 110
TRANSITION ALTITUDE
9000 FT

RADAR	125.100, 119.700, 124.450
APP	125.100, 119.700, 124.450
TWR	118.100
GND	121.700, 121.900
ATIS	128.000

TEHRAN/MEHRABAD
RWY 11L/R, 29L/R
PAXID 3A/3B

ALL DIRECTIONS ARE MAGNETIC.
LEVEL AND ELEVATIONS ARE IN FEET.
DISTANCES ARE IN NAUTICAL MILES.

TMA above FL200 class "A",
at FL 200 and below class "C".
CTR and ATZ class "D".



PAXID 3A DEP:

DEP RWY 29L/R - After take off turn left to intercept RDL 270, at 25 DME turn right to intercept RDL 328 FM RUS VOR/DME to PAXID and climb to cleared level.

PAXID 3B DEP:

DEP RWY 11L/R - After take off turn right to intercept RDL 270, at 25 DME turn right to intercept RDL 328 FM RUS VOR/DME to PAXID and climb to cleared level.

Note: As general, PAXID is usable for arrivals, therefore SIDs to PAXID are not normally used except as instructed explicitly by ATC.