

AERODROME CHART - ICAO

MASHHAD / SHAHID HASHEMI NEJAD

Scale 1 : 15000

200M

0

200

400

600

800M

500FT

0

500

1000

2500FT

VAR 4°E

Hotspot 1:
All aircraf on TWY C1, C2, A, B, Q, J must hold short of RWY 31L/13R.

Hotspot 2:
All landing aircraft from RWY 31R/13L must hold short of RWY 31L/13R on TWYs F and G.

Hotspot 3:
caution, unauthorized vehicle movement.

Aerodrome Elevation : 3266 FT			
Aerodrome Lighting			
13L	31R	13R	31L
SALS	PALS CAT I	SALS	SALS
RTHL	SFLS	RTHL	RTHL
PAPI	RTHL	PAPI	PAPI
REDL	PAPI	REDL	REDL
RENL	REDL	RENL	RENL
SWYL	RENL	SWYL	SWYL

ABN : FLG White, Green

Apron : INFO not AVBL

TWY Lighting	
Edge : All TWYs	Center Line : NIL

ATS Communication Facilities	
Service Designation	Frequency
TWR	118.100, 121.900
GND	121.700
ATIS	126.400
-	-

AD Reference Code : 4E

Displaced Threshold

NIL

RWY	Direction	Elevation	THR Coordinates	GUND	Bearing Strength (PCN) and Surface
13L	133.6°	3228 FT	361451.71N 0593735.23E	- 55 FT	60/F/B/X/T Asphalt
31R	313.6°	3260 FT	361326.45N 0593925.71E	- 55 FT	60/F/B/X/T Asphalt
13R	133.59°	3234 FT	361448.01N 0593727.83E	- 55 FT	60/F/B/X/T Asphalt
31L	313.61°	3266 FT	361320.29N 0593921.51E	- 55 FT	60/F/B/X/T Asphalt

VOR check point

TWY H : Coordinates: 361448.52N 0593731.16E, Radial: 303°, Distance: 1.54 NM

TWY C2 : Coordinates: 361317.85N 0593918.01E, Radial: 155°, Distance: 0.6 NM

TWY

Width : A is 35M, E is 27M, C1 and C2 are 23M, (B, C, C3, F, J, L, M, N, P, Q) are 30M, G is 35M, K is 15M, D and H are 85M.

Surface : TWYs A, C, C1 to C3, D, F, G, H, K and L: Asphalt. B, E, J, M, N, P and Q: concrete.

Strength (PCN) : TWYs A, C, C1 to C3, D, F, G, H and K: 60/F/B/X/T. B, E, J, Q: 70/R/B/W/T. others: INFO not AVBL.

Apron

Surface : Conceret

Strength (PCN) : 65/R/B/X/T

Dimensions : INFO not AVBL

Apron

Taxiway

Runway

Building

Hotspot

Isolated ACFT Parking Position

Deicing Pad

Under Construction

