

INSTRUMENT APPROACH
PROCEDURE TABULAR
DESCRIPTION

ZAHEDAN
RNP RWY 17R
CAT A/B/C/D

CODING INFORMATION FOR RNP APCH RWY 35L OIZH													
Serial Number	Path Descriptor	Waypoint Identifier	Function in Approach	COORDINATES	Fly-over	Course/Track M° (T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/ TCH (ft)	Navigation Specification
001	IF	ZH409	IAF	294434.6N 0604612.8E	-	-	-2.3	-	-	+10000	-210	-	RNP APCH
002	TF	ZH410	IF	293939.5N 0605004.5E	-	143(145.8)	-2.3	5.9	RIGHT	+7100	-	-	RNP APCH
003	TF	ZH411	FAF	293530.6N 0605317.8E	-	143(145.8)	-2.3	5	RIGHT	@6400	-	-	RNP APCH
004	TF	THR17R	-	292940.7N 0605408.0E	Y	170(172.8)	-2.3	5.9	-	+5220	-	-	RNP APCH
005	DF	ZH404	MATP (THR 35L)	292723.2N 0605427.8E	Y	170(172.8)	-2.3	2.3	RIGHT	+5500	-185	-	RNP APCH
006	DF	ZH408		292654.1N 0604845.6E	-	-	-2.3	-	RIGHT	+6000	-185	-	RNP APCH
007	TF	ZH409		294434.6N 0604612.8E	-	350(352.8)	-2.3	17.9	-	+10000	-210	-	RNP APCH
008	HM	ZH409	HLDG	294434.6N 0604612.8E	-	-	-2.3	-	-	+10000	-	-	RNP APCH