

AD 2. AERODROMES**OISS AD 2.1 AERODROME LOCATION INDICATOR AND NAME**
OISS - SHIRAZ / SHAHID DASTGHAIB International**OISS AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	<i>ARP coordinates and site at AD</i>	293225N 0523519E, 20 M from DVOR/DME and south of service road
2	<i>Direction and distance from (city)</i>	5 NM, E of Shiraz
3	<i>Elevation / Reference temperature</i>	4927 FT / 37.8°C
4	<i>MAG VAR / Annual change</i>	3° E (2017)
5	<i>AD Administration, address, telephone, telefax, telex, AFS</i>	Iranian Airports & Air Navigation Company (IAC) Shiraz / Shahid Dastghaib International Airport Postal code: 7158793136 P.O.BOX: 71555-666 Shiraz - Islamic Republic of Iran Tel : +9871 – 37218890- 9 Fax: +9871 - 37216969 Telex: NIL AFS:OISSYDYX
6	<i>Types of traffic permitted (IFR/VFR)</i>	IFR/VFR
7	<i>Remarks</i>	Website: Shiraz.airport.ir , Email: airportoffice@Shiraz.airport.ir

OISS AD 2.3 OPERATIONAL HOURS

1	<i>AD Administration</i>	H24
2	<i>Customs and immigration</i>	H24
3	<i>Health and sanitation</i>	H24
4	<i>AIS Briefing Office</i>	NIL
5	<i>ATS Reporting Office (ARO)</i>	H24
6	<i>MET Briefing Office</i>	NIL
7	<i>ATS</i>	H24
8	<i>Fuelling</i>	H24
9	<i>Handling</i>	H24
10	<i>Security</i>	H24
11	<i>De-icing</i>	H24
12	<i>Remarks</i>	NIL

OISS AD 2.4 HANDLING SERVICES AND FACILITIES

1	<i>Cargo - handling facilities</i>	Available by Iran Air, and Saman airport services
2	<i>Fuel / oil types</i>	Jet A1 - 100L
3	<i>Fueling facilities/capacity</i>	Jet A1 : 2 trucks, 45000 litres, 33 litres/sec, 1 truck 25000 litres, 13 litres/sec, 1 truck 20000 litres ; 15 litres/sec, No limitation 100LL: Available in 200 litres barrel
4	<i>De - icing facilities</i>	Available by Iran Aseman Airlines by prior coordination. it will be done at TWY A between TWYs A3 & A4
5	<i>Hangar space for visiting aircraft</i>	NIL
6	<i>Repair facilities for visiting aircraft</i>	NIL
7	<i>Remarks</i>	NIL

OISS AD 2.5 PASSENGER FACILITIES

1	<i>Hotels</i>	Available in the city
2	<i>Restaurants</i>	At AD and in the city
3	<i>Transportation</i>	Taxis
4	<i>Medical facilities</i>	First aids, ambulance at AD, Hospital in the city
5	<i>Bank and Post Office</i>	Available in the city, At AD only bank is available
6	<i>Tourist Office</i>	Available in the city & terminal
7	<i>Remarks</i>	NIL

OISS AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	<i>AD category for fire fighting</i>	CAT 8
2	<i>Rescue equipment</i>	Available in accordance with AD category for fire fighting
3	<i>Capability for removal of disabled aircraft</i>	Heavy duty crane and tow car/truck available
4	<i>Remarks</i>	NIL

OISS AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	<i>Types of clearing equipment</i>	2 blades fitted into truck
2	<i>Clearance priorities</i>	1- RWY 29L/11R 2- TWYs B4 and A4 3- Apron 4- RWY 29R/11L 5- Other TWYs
3	<i>Remarks</i>	→ 1 grader & 1 backhoe loader

OISS AD 2.8 APRONS, TAXIWAYS

1	<i>Apron surface and strength</i>	Surface: Concrete Strength: NIL
2	<i>Taxiway width, surface and strength</i>	Width: All TWYs 23M except the following: TWY A2: 29M; TWYs A3, A4, A5, G3, G4: 26M Surface: Asphalt Strength: Information not available
3	<i>Altimeter checkpoint Location and Elevation</i>	Information not available
4	<i>VOR checkpoint</i>	Coordinates: 293152.1N 0523638.0 E Radial: 113° ; Distance: 1.3 NM
5	<i>INS checkpoint</i>	Information not available
6	<i>Remarks</i>	Apron dimensions: 930 x 100 M

OISS AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	<i>Use of aircraft stand ID signs, TWY guide lines and parking guidance system of aircraft stands</i>	Taxi guidance signs at all intersections with TWY which are used by civil aircraft and RWY and at all holding position. Guide lines at apron. Nose-in guidance at aircraft stand.
2	<i>RWY and TWY markings and LGT</i>	RWY marking: Designation, THR, TDZ, centre line, edge & end. RWY lighting: See OISS AD 2.14 below. TWY marking: Centre line, edge, holding position at TWYs A1 to A7, B1, B2, B4, B5, B7 and RWY intersection. TWY lighting: See OISS AD 2.15 below.
3	<i>Stop bars</i>	NIL
4	<i>Remarks</i>	NIL

OISS AD 2.10 AERODROME OBSTACLES

<i>In approach / TKOF areas</i>			<i>In circling area and at AD</i>		<i>Remarks</i>
1			2		
<i>RWY/Area affected</i>	<i>Obstacle type Elevation/ HGT Markings/LGT</i>	<i>Coordinates</i>	<i>Obstacle type Elevation / HGT Markings/LGT</i>	<i>Coordinates</i>	
a	b	c	a	b	
11R 29L	ILS GP 29L antenna 4921 FT AMSL LGTD	293145.8N 0523619.7E	NDB antenna 4970 FT AMSL LGTD	293144.3N 0523557.9E	
11R / APCH 29L / TKOF	LLZ 29L antenna 4946 FT AMSL LGTD	293248.6N 0523354.0E	Mast 5455 FT AMSL NIL	292647N 0523853E	
			Mast 5758 FT AMSL NIL	292701N 0523844E	
			Com mast 5023 FT AMSL LGTD	293159N 0523445E	
			10 Flood lights 4977 FT AMSL NIL	Mean PSN: 293244N 0523523E	
			Tower building 5043 FT AMSL LGTD	293237N 0523553E	

OISS AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	<i>Associated MET Office</i>	Shiraz
2	<i>Hours of service</i> <i>MET Office outside hours</i>	H24 --
3	<i>Office responsible for TAF preparation</i> <i>Periods of validity</i>	Tehran Intervals of 6 hour and validity of 30hour
4	<i>Type of landing forecast</i> <i>Interval of issuance</i>	Trend 2 HR
5	<i>Briefing/consultation provided</i>	In person and by telephone: +9871 37212244
6	<i>Flight documentation</i> <i>Language(s) used</i>	Charts, abbreviated plain language text English/Persian
7	<i>Charts and other information available for briefing or consultation</i>	S, U, P
8	<i>Supplementary equipment available for providing information</i>	NIL
9	<i>ATS units provided with information</i>	Shiraz TWR; Shiraz APP; Shiraz Radar
10	<i>Additional information (limitation of service, etc.)</i>	NIL

OISS AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

<i>Designations RWY NR</i>	<i>TRUE BRG</i>	<i>Dimensions of RWY (M)</i>	<i>Strength(PCN) and surface of RWY and SWY</i>	<i>THR coordinates THR geoid undulation</i>	<i>THR elevation and highest elevation of TDZ of precision APP RWY</i>
1	2	3	4	5	6
11L	114.45°GEO	4334 x 45	85/F/C/W/T Asphalt	293256.90N 0523413.60E GUND -31 FT	THR 4921.2 FT
29R	294.47°GEO	4334 x 45	85/F/C/W/T Asphalt	293158.61N 0523640.12E GUND -31 FT	THR 4873.1 FT
11R	114.46°GEO	4272 x 45	80/F/C/W/T Asphalt	293242.56N 0523408.65E GUND -31 FT	THR 4926.5 FT
29L	294.48°GEO	4272 x 45	80/F/C/W/T Asphalt	293145.09N 0523633.08E GUND -31 FT	THR 4869.7 FT
<i>Slope of RWY - SWY</i>	<i>SWY dimensions (M)</i>	<i>CWY dimensions (M)</i>	<i>Strip dimensions (M)</i>	<i>OFZ</i>	<i>Remarks</i>
7	8	9	10	11	12
0.34 %	350 x 45	350 x 150	NIL	NIL	- Distance between parallel RWY centre lines is 457 M. - First 305 M of each RWY is concrete. - AD Code Letter / Number : 4E
0.34 %	443 x 45	443 x 150	NIL	NIL	
0.40 %	302 x 45	302 x 150	NIL	NIL	
0.40 %	350 x 45	350 x 150	NIL	NIL	

OISS AD 2.13 DECLARED DISTANCES

RWY Designator	TORA(M)	TODA(M)	ASDA(M)	LDA(M)	Remarks
11L	4334	4684	4684	4334	NIL
29R	4334	4777	4777	4334	NIL
11R	4272	4574	4574	4272	NIL
29L	4272	4622	4622	4272	NIL
11L	3247	3597	3597	-	Take-off from intersection A5 & B5
11L	3820	4170	4170	-	Take-off from intersection A6
29R	3078	3521	3521	-	Take-off from intersection A2 & B2
29R	2437	2880	2880	-	Take-off from intersection A3
11R	3251	3553	3553	-	Take-off from intersection B5
29L	3012	3362	3362	-	Take-off from intersection B2 & C2

Pilot is responsible to determine the required runway length when requesting intersection take-off.

Intersection take-off will not be available when:

- a) visibility is less than 1200M or
- b) braking action is reported below GOOD or
- c) full runway length is not available due to WIP.

OISS AD 2.14 APPROACH AND RUNWAY LIGHTING

<i>RWY Designator</i>	<i>APCH LGT type LEN INTST</i>	<i>THR LGT colour WBAR</i>	<i>VASIS (MEHT) PAPI</i>	<i>TDZ LGT LEN</i>	<i>RWY Centre Line LGT LEN, spacing, colour INTST</i>	<i>RWY edge LGT LEN, spacing colour, INTST</i>	<i>RWY End LGT colour WBAR</i>	<i>SWY LGT LEN colour</i>	<i>Remarks</i>
<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>	<i>6</i>	<i>7</i>	<i>8</i>	<i>9</i>	<i>10</i>
11L	SALS 420M LIH	Green Supplemented by WBAR	NIL	NIL	NIL	4332 M 60 M white LIH	Red Supplemented by WBAR	350M RED LIH	NIL
29R	PALS 900M LIH	Green Supplemented by WBAR	PAPI Left/3.0° (19.4 M / 63.65 FT)	NIL	NIL	4332 M 60 M white LIH	Red Supplemented by WBAR	443M RED LIH	NIL
11R	SALS 420M LIH	Green Supplemented by WBAR	NIL	NIL	NIL	4272M 60M White, LIH	Red Supplemented by WBAR	302M RED LIH	NIL
29L	PALS 900M LIH	Green Supplemented by WBAR	PAPI Left /3° (19.4 M / 63.65 FT)	NIL	NIL	4272M 60M White, LIH	Red Supplemented by WBAR	350M RED LIH	NIL

OISS AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	<i>ABN location, characteristics and hours of operation</i>	On top of the control Tower building, FLG G and W, EV 2 sec. HN and during IMC
2	<i>LDI location and LGT</i> <i>Anemometer location and LGT</i>	NIL 293235.5N, 0523531.4E & 293158.4N, 0523618.8E, LGTD
3	<i>TWY edge and centre line lighting</i>	Edge: TWYs A, A1 to A5, A7, B1, B2, B4, B5, B7, G3 and G4 Centre line : NIL
4	<i>Secondary power supply/switch-over time</i>	Available Switch-over time: 10 - 15 sec
5	<i>Remarks</i>	NIL

OISS AD 2.16 HELICOPTER LANDING AREA

NIL

OISS AD 2.17 ATS AIRSPACE

1	<i>Designation and lateral limits</i>	Shiraz CTR : A circle, radius 30 NM centered at 293224.6N 0523519.6E (DVOR/DME)	Shiraz ATZ: A circle , radius 7 NM centered at 293225N 0523519E (ARP)
2	<i>Vertical limits</i>	11500 FT AMSL	8500 FT AMSL
3	<i>Airspace classification</i>	D	
4	<i>ATS unit call sign Language(s)</i>	Shiraz APP/Radar English / Persian	Shiraz TWR English / Persian
5	<i>Transition altitude</i>	13000 FT AMSL	
6	<i>Remarks</i>	NIL	

OISS AD 2.18 ATS COMMUNICATION FACILITIES

<i>Service designation</i>	<i>Call sign</i>	<i>Frequency</i>	<i>Hours of operation</i>	<i>Remarks</i>
1	2	3	4	5
APP & RADAR	Shiraz Approach &Shiraz Radar	119.000 MHZ	H24	Emergency FREQ Military aircraft Military aircraft Military aircraft Military/Emergency Military aircraft/UDF
		125.400 MHZ	H24	
		121.500 MHZ	H24	
		362.300 MHZ	H24	
		344.000 MHZ	H24	
		385.400 MHZ	H24	
		243.000 MHZ	H24	
		317.500 MHZ	H24	
TWR	Shiraz Tower	118.100 MHZ	H24	Emergency FREQ Military aircraft Military aircraft
		121.500 MHZ	H24	
		275.800 MHZ	H24	
		257.800 MHZ	H24	
GND	Shiraz Ground	121.900 MHZ	H24	For vehicular movements
		121.750 MHZ	H24	
ATIS (INFO)	Shiraz Information	127.000 MHZ	H24	
UDF unusable in FLW area: 1- 010°-070° beyond 6 NM BLW 9000 FT MSL & beyond 20 NM BLW FL 190. 2- 070°-130° beyond 32 NM BLW FL 190. 3- 130°-250° beyond 20 NM BLW FL 180. 4- 250°-010° beyond 25 NM BLW FL 170.				

5- In case of radio communication failure, a helicopter shall maintain 300 FT AGL before 5NM from SYZ DVOR/DME, then makes a normal traffic pattern at 300 FT AGL to landing area without crossing Runways and Finals. In such cases if crossing is required, helicopters shall cross final approach RWY 29L/R beyond 5NM (approximately on the edge of Maharloo Lake) at 300 FT AGL and proceed to parking area while maintaining separation with other traffic. Shiraz ATC shall be informed by the pilot or operator as soon as possible after landing.

6- Normally, RWY 29L assigned for arrivals and RWY 29R for departures.

7- In order to maximize runway capacity, aircraft shall minimize runway occupancy time. Departing aircraft on receipt of the line-up clearance, shall taxi to position as soon as possible. Cockpit checks shall be completed prior to line up . Aircraft that cannot comply with these requirements shall notify ATC as soon as possible.

8- Aircraft taxiing on apron shall use minimum power due to proximity of terminal sand installation.

9- To avoid FOD on maneuvering area heavy aircraft shall taxi with minimum total jet blast effect at all times. For this purpose, B747 and B777 may be instructed to backtrack runways.

10- Due to high terrain, aircraft under radar vectoring shall not cross final approach track unless explicitly instructed by ATC.

11- Shiraz radar equipment is not capable of detecting adverse weather. When under radar vectoring, it is the responsibility of the pilot-in-command to advise ATC if weather deviation is required.

OISS AD 2.21 NOISE ABATEMENT PROCEDURES

1 - RWY 29L/R is not used for take-off during 1930-0230(1830-0130), except tailwind component for RWY 11L/R is 5KT or more, or traffic/adverse weather condition.

2 - Aircraft making Visual approach between 1930-0230(1830-0130) should not descend below 8000 FT AMSL until passing middle of right downwind RWY 29 except in emergency situation.

3 - Visual Right turn for departing aircraft from RWY 29L/R is not authorized between 1930-0230(1830-0130).

OISS AD 2.22 FLIGHT PROCEDURES

1- Traffic pattern is defined as below:

- a. For fighter and heavy fixed-wing ACFT 6500 feet,
- b. For other fixed-wing ACFT 6000 feet and
- c. For helicopter 5500 feet.

Note: see AD 1.1.

2- Initial contact instructions for departures

Departing IFR/VFR aircraft shall contact Shiraz ground on 121.90 MHz, 5 to 10 minutes prior to start-up and pass the following information:

- Desired level
- ATIS code letter and QNH
- Route of flight and significant points for VFR flights
- Estimated elapse time to destination for VFR flights.
- Any other necessary information or request such as needs for De-ice/Anti-ice.

3- RCF procedure

The following RCF procedures shall be followed during IMC or VMC unless other factors such as emergencies, weather conditions, terrain clearance, etc. dictate otherwise:

- 1) **Arriving IFR aircraft (during STAR or vectoring)**
 - Squawk 7600.

When approach clearance is not received:

- a. Maintain last assigned level or 13000 ft, whichever is higher.
- b. Proceed to SYZ DVOR/DME and join holding, then execute a normal approach procedure to the arrival runway.

When approach clearance is already received:

Continue approach to the assigned and acknowledged runway.

2) Departing IFR aircraft (during SID or vectoring)

- Squawk 7600

Before 25 NM from SYZ DVOR/DME:

- Maintain last assigned level or 12000 ft, whichever is higher.

After 25 NM from SYZ DVOR/DME:

- Maintain last assigned level or Minimum Safe Level, whichever is higher, for 7 minutes, then climb to filed flight plan level.
- Maintain last assigned heading or track for 3 minutes, then continue according to current flight plan.

If returning to OISS for non-emergency reasons:

Continue SID to SYZ climb to 11500 ft, then comply with RCF procedure for arriving IFR flights.

OISS AD 2.23 ADDITIONAL INFORMATION

- 1- Intensive birds' accumulation exists over the field and in the vicinity of AD.
- 2- Strolling animals exist on the movement area.
- 3- Heavy aircraft are permitted to make 180° turn only at the end of RWY in use.
- 4- Net barrier:
 - RWY 29L: PSN at SWY RWY 29L, 69 M before THR RWY 11R;
 - RWY 11L: PSN at SWY RWY 11L, 69 M before THR RWY 29R, and will be engaged by prior arrangement, HGT during engagement is 10.5 FT AGL.
- 5- Hook barrier:
 - RWY 29L: PSN at SWY RWY 29L, 50 M before THR RWY 11R and
It will be engaged by prior arrangement. HGT during engagement is 11 CM AGL.
 - RWY 11L: first one PSN at SWY RWY 11L, 60 M before THR RWY 29R and
second one PSN at 910 M after THR RWY 11L.
They will be engaged by prior arrangement. HGT during engagement is 11 CM AGL.
- 6- Different types of obstacle such as trees, vehicles and trucks with MAX HGT 17 FT exist at the north of apron extremity.
- 7- Anti-icing and de-icing area located at TWY A between TWYs A3 & A4 for aircraft with a wing span less than 35m. Anti-icing and De-icing of aircraft with more than 35m of wing span shall be carried out at the related stands according to Shiraz aircraft parking chart.
- 8- Isolated aircraft parking position located at B6.
- 9- TWY B6 closed.
- 10- Hot spot:
 - 1- After landing 29L/11R hold short of RWY 29R/11L and look out for departing traffic.
 - 2- Taxing aircraft look out for landing and departing traffic on RWY 29L/11R

OISS AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart – ICAO -----	AD 2 OISS ADC
Aircraft Parking / Docking Chart -----	AD 2 OISS APDC 1 AD 2 OISS APDC 2
Aerodrome Obstacle Chart — ICAO Type A -----	AD 2 OISS AOC 1 AD 2 OISS AOC 2
← Radar Minimum Altitude Chart - ICAO-----	AD 2 OISS ASMAC 1 AD 2 OISS ASMAC 2
Standard Departure Chart - Instrument – ICAO -----	AD 2 OISS SID 1-1 AD 2 OISS SID 1-2 AD 2 OISS SID 1-3 AD 2 OISS SID 1-4 AD 2 OISS SID 1-5 AD 2 OISS SID 1-6 AD 2 OISS SID 1-7 AD 2 OISS SID 1-8 AD 2 OISS SID 1-9 AD 2 OISS SID 1-10 AD 2 OISS SID 1-11 AD 2 OISS SID 1-12 AD 2 OISS SID 2-1 AD 2 OISS SID 2-2 AD 2 OISS SID 2-3 AD 2 OISS SID 2-4 AD 2 OISS SID 2-5 AD 2 OISS SID 2-6 AD 2 OISS SID 2-7 AD 2 OISS SID 2-8 AD 2 OISS SID 2-9 AD 2 OISS SID 2-10
Standard Arrival Chart - Instrument - ICAO -----	AD 2 OISS STAR 1-1 AD 2 OISS STAR 1-2 AD 2 OISS STAR 1-3 AD 2 OISS STAR 1-4 AD 2 OISS STAR 1-5 AD 2 OISS STAR 1-6 AD 2 OISS STAR 1-7 AD 2 OISS STAR 1-8 AD 2 OISS STAR 1-9 AD 2 OISS STAR 1-10 AD 2 OISS STAR 1-11

AD 2 OISS STAR 1-12

AD 2 OISS STAR 1-13

AD 2 OISS STAR 1-14

AD 2 OISS STAR 1-15

AD 2 OISS STAR 1-16

AD 2 OISS STAR 1-17

AD 2 OISS STAR 1-18

AD 2 OISS STAR 1-19

Instrument Approach Chart - ICAO ----- AD 2 OISS IAC 1-1

AD 2 OISS IAC 1-2

AD 2 OISS IAC 1-3

AD 2 OISS IAC 2-1

AD 2 OISS IAC 2-2

AD 2 OISS IAC 2-3

AD 2 OISS IAC 2-4

AD 2 OISS IAC 4-1